



US011172711B2

(12) **United States Patent**  
**Randall et al.**

(10) **Patent No.:** **US 11,172,711 B2**  
(45) **Date of Patent:** **\*Nov. 16, 2021**

(54) **BRASSIERE AND FRONT PANEL FOR BRASSIERE**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(71) Applicant: **Mast Industries (Far East) Limited,**  
Kowloon (HK)

(56) **References Cited**

(72) Inventors: **Tracey Randall,** New York, NY (US);  
**Ursula Giovanna Todaro,** Glendale,  
NY (US); **Zhenqiang Liu,** Kwai Chung  
(HK); **Tara Sweeney,** Hoboken, NJ  
(US)

U.S. PATENT DOCUMENTS

1,472,796 A 9/1922 Fritz  
2,285,967 A \* 6/1942 Hardy ..... B29C 51/08  
264/292

(Continued)

(73) Assignee: **Mast Industries (Far East) Limited,**  
Kowloon (HK)

FOREIGN PATENT DOCUMENTS

CN 201135143 Y 10/2008  
CN 201142941 Y 11/2008

(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

This patent is subject to a terminal dis-  
claimer.

Under Armour, Armour High Bra, website, last accessed Mar. 31,  
2017, available at <https://www.underarmour.com/enus/womensuaarmourhighbra/pid1259953> (admitted prior art).

(Continued)

(21) Appl. No.: **16/851,741**

(22) Filed: **Apr. 17, 2020**

(65) **Prior Publication Data**  
US 2020/0237029 A1 Jul. 30, 2020

*Primary Examiner* — Jocelyn Bravo  
(74) *Attorney, Agent, or Firm* — Andrus Intellectual  
Property Law, LLP

**Related U.S. Application Data**


(62) Division of application No. 15/593,557, filed on May  
12, 2017, now Pat. No. 10,660,377.  
(Continued)

(51) **Int. Cl.**  
*A41C 3/14* (2006.01)  
*A41C 3/00* (2006.01)  
(Continued)

(57) **ABSTRACT**

(52) **U.S. Cl.**  
CPC ..... *A41C 3/14* (2013.01); *A41C 3/0007*  
(2013.01); *A41C 3/0057* (2013.01); *A41C 3/02*  
(2013.01); *A41C 3/128* (2013.01); *A41C 3/142*  
(2013.01)

A brassiere includes bra cups holding a wearer's breasts. A  
shaping foam layer is sandwiched between outer and inner  
layers of each bra cup and extends from a lower to an upper  
edge of each cup. A support shelf assembly spans across a  
lower portion of each bra cup and includes a support  
component located proximate the lower edge of the cups, a  
non-stretch stabilizer fabric layer spanning between both  
cups and along a full length of the support component, and  
a supportive foam layer spanning between both cups and  
along the support component. The inner, outer, shaping  
foam, stabilizer fabric, and supportive foam layers span  
across a center gore that connects the bra cups to form a front  
panel of the brassiere. The support shelf assembly is molded  
(Continued)



between the inner layer and the shaping foam layer and is an embedded, integral part of the front panel.

**20 Claims, 8 Drawing Sheets**

**Related U.S. Application Data**

(60) Provisional application No. 62/337,027, filed on May 16, 2016.

(51) **Int. Cl.**  
*A41C 3/02* (2006.01)  
*A41C 3/12* (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,719,301 A 10/1955 Witkower  
 2,769,180 A 11/1956 Tareau et al.  
 2,817,842 A 12/1957 Block et al.  
 2,834,352 A 5/1958 Ullian  
 2,844,151 A 7/1958 Lemons  
 3,196,460 A 7/1965 Halsted  
 3,202,565 A 8/1965 Loftin  
 3,221,747 A 12/1965 Blair  
 3,266,495 A \* 8/1966 Sachs ..... A41C 3/10  
 450/55  
 3,642,009 A 2/1972 Nobbs  
 3,799,174 A 3/1974 Howard  
 3,934,593 A 1/1976 Mellinger  
 4,080,416 A 3/1978 Howard  
 4,289,137 A 9/1981 Dell et al.  
 4,325,378 A 4/1982 Wilkinson  
 4,340,064 A 7/1982 Vale  
 4,538,614 A 9/1985 Henderson  
 4,945,571 A 8/1990 Calvert  
 4,992,074 A 2/1991 Diaz  
 5,098,330 A 3/1992 Greenberg  
 5,221,227 A 6/1993 Michels  
 5,527,202 A 6/1996 Morgan et al.  
 5,660,577 A \* 8/1997 Modena ..... A41C 3/00  
 450/86  
 5,690,537 A 11/1997 Kalmus  
 6,000,994 A 12/1999 Salotto  
 6,019,662 A 2/2000 Fildan  
 6,083,080 A 7/2000 Lawson et al.  
 6,106,363 A 8/2000 Werner  
 6,165,045 A 12/2000 Miller et al.  
 6,176,761 B1 1/2001 Underhill  
 6,231,423 B1 5/2001 Deal et al.  
 6,397,391 B2 6/2002 Demarco  
 6,425,800 B1 7/2002 Huang  
 6,439,959 B1 8/2002 Magrone et al.  
 6,447,365 B1 9/2002 Powell et al.  
 6,645,040 B2 11/2003 Rabinowicz et al.  
 6,685,534 B2 2/2004 Mitchell et al.  
 6,688,942 B2 2/2004 Holliday  
 6,695,677 B1 \* 2/2004 Lin ..... A41C 3/0007  
 450/41  
 6,811,464 B2 11/2004 Li  
 6,824,444 B2 11/2004 Huang  
 6,846,219 B2 1/2005 Moyer  
 6,896,580 B2 5/2005 Falla et al.  
 6,966,815 B2 11/2005 Weinerth  
 6,986,696 B1 1/2006 Jagaric et al.  
 6,988,931 B1 1/2006 Martinet et al.  
 6,997,775 B2 2/2006 Jagaric et al.  
 7,048,606 B1 5/2006 Martinet et al.  
 7,052,360 B2 5/2006 Lau  
 7,131,888 B2 11/2006 Hsu  
 7,241,199 B2 7/2007 Huang  
 7,309,276 B2 12/2007 Legaspi et al.  
 7,311,583 B2 12/2007 Jagaric et al.

7,390,239 B1 6/2008 Huang  
 7,407,427 B2 8/2008 Liu  
 7,442,110 B2 10/2008 Gaudet et al.  
 7,458,877 B2 12/2008 Yu  
 7,563,152 B2 7/2009 Liu  
 7,604,526 B2 10/2009 Liu  
 7,690,965 B2 4/2010 Falla et al.  
 RE41,654 E 9/2010 Struble et al.  
 7,833,082 B2 11/2010 Bugada  
 7,862,401 B2 1/2011 Watrin et al.  
 7,871,305 B2 1/2011 Cohen et al.  
 8,113,908 B1 \* 2/2012 Modena ..... A41C 3/0007  
 450/39  
 8,113,909 B2 2/2012 Liu  
 8,167,678 B2 5/2012 Castellano  
 8,419,502 B2 4/2013 Liu  
 8,419,503 B2 4/2013 Zhang  
 8,585,459 B2 11/2013 Martinet et al.  
 8,747,184 B2 6/2014 Liu  
 8,747,185 B1 6/2014 Evans, Sr.  
 8,864,549 B2 10/2014 Mckee  
 9,198,468 B2 12/2015 Mcneeley et al.  
 9,210,955 B2 12/2015 Dandapure et al.  
 9,226,530 B1 1/2016 Silverman et al.  
 9,237,772 B2 1/2016 Mckeen  
 9,241,514 B2 1/2016 Shearer  
 9,392,822 B2 7/2016 Mckeen  
 9,402,424 B2 8/2016 Roy  
 9,480,287 B2 11/2016 Black et al.  
 9,578,901 B2 \* 2/2017 Randall ..... A41C 3/0057  
 9,622,516 B2 4/2017 Lau  
 10,231,492 B1 3/2019 Bastug  
 10,271,585 B2 4/2019 Mckeen  
 2001/0019933 A1 9/2001 Wagner  
 2003/0082994 A1 5/2003 Mitchell et al.  
 2003/0092355 A1 \* 5/2003 Rabinowicz ..... A41C 5/00  
 450/1  
 2003/0232571 A1 12/2003 Weinerth  
 2005/0164602 A1 7/2005 Armstrong et al.  
 2006/0046614 A1 3/2006 Hsu  
 2006/0105674 A1 5/2006 Lau  
 2006/0240743 A1 10/2006 Mitchell  
 2007/0155283 A1 7/2007 Mcqueer  
 2008/0090491 A1 \* 4/2008 Liu ..... A41C 3/0014  
 450/39  
 2008/0153388 A1 6/2008 Liu  
 2008/0305714 A1 12/2008 Sobah-Wilhelm  
 2009/0098803 A1 4/2009 Reinisch et al.  
 2009/0197509 A1 8/2009 Fildan et al.  
 2009/0233523 A1 9/2009 Pardo et al.  
 2009/0233524 A1 9/2009 Cohen  
 2009/0247047 A1 10/2009 Avalos-Dessner et al.  
 2010/0015886 A1 1/2010 Waitz et al.  
 2010/0056022 A1 5/2010 Liu  
 2010/0317256 A1 12/2010 Zhang  
 2011/0104985 A1 5/2011 Linder et al.  
 2011/0287691 A1 11/2011 Hu  
 2011/0300774 A1 12/2011 Smith  
 2012/0094575 A1 4/2012 Sokolowski et al.  
 2012/0122370 A1 5/2012 Heath et al.  
 2012/0171929 A1 7/2012 Cheung  
 2012/0184180 A1 7/2012 Hu  
 2012/0184181 A1 7/2012 Liu  
 2013/0165017 A1 6/2013 Liu  
 2014/0213145 A1 7/2014 Mckeen  
 2014/0256221 A1 9/2014 Liang  
 2014/0302746 A1 10/2014 Warren et al.  
 2014/0329438 A1 11/2014 Horii  
 2014/0370784 A1 \* 12/2014 Chen ..... A41C 5/005  
 450/41  
 2015/0111466 A1 4/2015 Martinet et al.  
 2015/0264982 A1 \* 9/2015 Randall ..... A41C 3/0057  
 450/52  
 2016/0044971 A1 \* 2/2016 Randall ..... A41C 3/0057  
 450/39  
 2016/0058075 A1 3/2016 Dandapure et al.  
 2016/0309795 A1 10/2016 Shearer  
 2016/0309797 A1 10/2016 Mckeen  
 2017/0095010 A1 4/2017 Fildan et al.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

2017/0188638 A1 7/2017 Liu  
 2017/0226691 A1 8/2017 Farmer et al.  
 2017/0318867 A1 11/2017 Wiesman  
 2017/0360118 A1 12/2017 Randall et al.  
 2018/0055097 A1 3/2018 Delaney  
 2018/0242653 A1 8/2018 Brandt et al.  
 2018/0249767 A1 9/2018 Begriche et al.

FOREIGN PATENT DOCUMENTS



CN 202077593 U 12/2011  
 CN 103269610 A 8/2013  
 CN 104544594 A 4/2015  
 CN 102215707 B 4/2016  
 CN 105473015 A 4/2016  
 CN 205624537 U 10/2016  
 CN 106136350 A 11/2016

EP 1872674 A1 1/2008  
 EP 2153739 A1 2/2010  
 EP 2695535 A1 2/2014  
 WO WO 2003033796 A1 4/2003  
 WO WO 2008020327 A2 2/2008

OTHER PUBLICATIONS

Reebok, Hero Racer Bra 2.0, website, last accessed Mar. 31, 2017, available at <http://www.reebok.com/US/reebokheroracerbra2.0/AJ2562.html> (admitted prior art).  
 Lululemon, Black Go Steady Bra, website, last accessed Mar. 31, 2017, available at <https://www.amazon.com/LululemonBlackGoSteadyBra/dp/B019JCI2C2> (admitted prior art).  
 Extended European Search Report issued in corresponding EP Application No. 17171153.4, dated Nov. 3, 2017.  
 Search Report issued in corresponding Chinese Application No. 201710346950.3, dated Oct. 10, 2018.

\* cited by examiner






FIG. 3




FIG. 5




FIG. 4




FIG. 7





FIG. 6

FIG. 8








FIG. 9




FIG. 10






FIG. 11



1

**BRASSIERE AND FRONT PANEL FOR  
BRASSIERE**CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a division of U.S. application Ser. No. 15/593,557, filed on May 12, 2017, which claims the benefit of U.S. Provisional Application Ser. No. 62/337,027, filed on May 16, 2016, and both of which applications are hereby incorporated by reference herein.

## FIELD

The present application relates to brassieres, and applies to both sports bras and lingerie.

## BACKGROUND

U.S. Pat. No. 8,747,184 discloses a support structure for placement in a lower periphery of a breast cup for a brassiere. The support structure includes a support component shaped to follow the curve of at least the underside of a wearer's breast. The support component includes a first region formed by a first polymer material and a second region formed by a second polymer material, wherein the first polymer material is harder than the second polymer.

Chinese Utility Model Publication No. CN205624537U discloses a cup for a bra comprising a foam-fabric inner layer for contact with the skin, characterized in that an outer sandwich cloth layer is provided on the side of the foam-fabric inner layer away from the skin. An inner steel ring is sandwiched between the inner edges of the foam-fabric inner layer and the outer sandwich cloth layer. The outer sandwich cloth layer has at least two fabric layers and a support comprising hot melt yarn between the two fabric layers.

## SUMMARY

This Summary is provided to introduce a selection of concepts that are further described below in the Detailed Description. This Summary is not intended to identify key or essential features of potentially claimed subject matter, nor is it intended to be used as an aid in limiting the scope of potentially claimed subject matter.

According to one example of the present disclosure, a front panel for a brassiere includes a pair of bra cups, each bra cup in the pair of bra cups configured to hold one of a wearer's breasts. An inner layer of each bra cup is configured to contact the wearer's skin and an outer layer of each bra cup opposes the inner layer. A support shelf assembly spans across at least a lower portion of each bra cup. The support shelf assembly comprises a plastic support component located proximate a lower edge of each respective bra cup, a non-stretch stabilizer fabric layer spanning between both bra cups and along a full length of the support component, and a first supportive foam layer spanning between both bra cups and along the support component. The support shelf assembly is molded between the inner and outer layers of each bra cup such that the support shelf assembly is an embedded, integral part of the front panel.

According to another example of the present disclosure, a brassiere includes a pair of bra cups, each bra cup in the pair of bra cups configured to hold one of a wearer's breasts. An inner layer of each bra cup is configured to contact the wearer's skin and an outer layer of each bra cup opposes the

2

inner layer. A shaping foam layer is sandwiched between the outer layer and the inner layer of each bra cup. The shaping foam layer extends from a lower edge of each bra cup to an upper edge of each bra cup. A support shelf assembly spans across at least a lower portion of each bra cup. The support shelf assembly comprises a support component located proximate the lower edge of each respective bra cup, a non-stretch stabilizer fabric layer spanning between both bra cups and along a full length of the support component, and a first supportive foam layer spanning between both bra cups and along the support component. The inner layer, outer layer, and shaping foam layer of each bra cup and the stabilizer fabric layer and first supportive foam layer of the support shelf assembly span across a center gore that connects the bra cups to form a front panel of the brassiere. The support shelf assembly is molded between the inner layer and the shaping foam layer of each bra cup such that the support shelf assembly is an embedded, integral part of the front panel.

## BRIEF DESCRIPTION OF THE DRAWINGS

Examples of brassieres, front panels for brassieres, and methods for manufacturing brassieres are described with reference to the following figures. These same numbers are used throughout the figures to reference like features and like components.

FIG. 1 illustrates one example of a front half of a sports bra according to the present disclosure.

FIG. 2 illustrates one example of a back half of the sports bra of FIG. 1.

FIGS. 3-7 illustrate several examples of cross sections of a bra cup for use in a bra according to the present disclosure.

FIG. 8 illustrates the layers of the bra cup of FIG. 3 as they would be placed in a mold for molding the cups of the sports bra.

FIG. 9 illustrates the layers of the bra cup of FIG. 4 as they would be placed in a mold for molding the cups of the sports bra.

FIG. 10 illustrates a perspective view of a sports bra according to the present disclosure as worn by a wearer.

FIG. 11 illustrates an alternative embodiment of a sports bra according to the present disclosure as worn by a wearer.

FIG. 12 illustrates a lingerie-type bra according to the present disclosure.

FIG. 13 illustrates a cross-sectional view of the area noted in FIG. 12.

## DETAILED DESCRIPTION

A brassiere (bra) pad construction for incorporation into a bra cup of a sports bra or a lingerie-type bra includes an outer layer comprising a spacer fabric and an inner layer comprising a different type of fabric. One or more layers of foam are molded and/or laminated to an inner face of the spacer fabric. A plastic support component is molded between the one or more layers of foam and/or the spacer fabric. The support component is part of a support shelf assembly that extends along a lower edge of a front panel of the bra. Various examples will be described herein below.

FIG. 1 illustrates a front portion of a sports bra 10 according to the present disclosure. The sports bra 10 includes a front panel 11 having a pair of bra cups 12a, 12b and a plunging neckline 14. Each bra cup 12a, 12b in the pair of bra cups is configured to hold one of a wearer's breasts (see FIGS. 10 and 11). The neckline 14 plunges to a central connection area known as a center gore 16, which connects

the bra cups **12a**, **12b**. Laterally outer edges **13a**, **13b** of each of the bra cups **12a**, **12b** are connected to underarm areas **18a**, **18b**. Upper edges **15a**, **15b** of the bra cups **12a**, **12b** are coupled to straps **20a**, **20b**, for example by fabric pieces **19a**, **19b**. In another example, the straps **20a**, **20b** can be directly connected to the upper edges **15a**, **15b** of the bra cups **12a**, **12b**. The straps **20a**, **20b** continue to the back portion of the sports bra **10**, which is shown in FIG. 2, and there connect to wings **22a**, **22b**, which make up the underarm areas **18a**, **18b**, respectively. As shown, the straps **20a**, **20b** connect to one another in a racer back shape; however, a T-shape or another shape could be provided. In an alternative embodiment, the straps **20a**, **20b** continue straight down to the wings **22a**, **22b**. The straps **20a**, **20b** may be made of an elastic material. As shown herein, the straps **20a**, **20b** are adjustable; however, the length of the straps **20a**, **20b** could alternatively be fixed.

A torso band **24** runs around the lower edge of the sports bra **10**, is coupled to lower edges **17a**, **17b** of the bra cups **12a**, **12b**, and includes a clasp or connector **26** in the back of the bra **10**, where the wings **22a**, **22b** of the sports bra **10** can be partially disconnected from and reconnected to one another in order to provide a desired fit around a wearer's torso. The connector **26** can be Velcro, hook and eye, snaps, or any other type of connector known to those having ordinary skill in the art. The torso band **24** can be made of an elastic material to provide stretch as the wearer moves or pulls the sports bra **10** over her head. The torso band **24** can be used to provide a finished edge for the bottom of the bra cups **12a**, **12b** and wings **22a**, **22b**, such as if the torso band **24** is folded in half so as to overlap the bottom edge of the sports bra **10**. Alternatively, the elastic torso band can be connected to only an outer or an inner face of the bottom edge of the sports bra **10**.

Note that the extent of the front panel **11** is also defined by the upper edges **15a**, **15b** of the bra cups **12a**, **12b**, the outer edges **13a**, **13b** of the bra cups **12a**, **12b**, and the lower edges **17a**, **17b** of the bra cups **12a**, **12b**. As will be described herein below, the front panel can be formed of layers of single, continuous sheets of fabric and foam, some of which have the same extent as the outline of the front panel **11** shown herein. This creates a strong, supportive front panel **11** for the sports bra **10**, which provides the necessary support and motion control for the wearer's breasts during exercise, as well as makes the front panel **11** easy to manufacture.

FIG. 3 shows a cross section through the bra cup **12a** of FIG. 1, taken along the line III-III. Although this cross section is taken close to the underarm area **18a** of the sports bra **10**, this cross section is essentially the same across the entire bra cup **12a**, except for relative dimensional changes in the thickness, height, and curvature of the bra cup **12a**. Additionally, it should be noted that the cross section through the bra cup **12b** is identical, although it will not be described separately herein. In fact, the bra cup **12b** is a mirror image of the bra cup **12a**, and therefore any description of the bra cup **12a** applies in kind to the bra cup **12b**. FIG. 3 shows how the bra cup **12a** has two sides. Specifically, an outer side **28** faces away from the wearer when the sports bra **10** is being worn. An inner side **30** faces the wearer and touches the wearer's skin when the sports bra **10** is being worn.

Starting at the inner side **30**, the bra cup **12a** includes an inner layer **50** configured to contact the wearer's skin. In the present example, the inner layer **50** of the bra cup **12a** comprises liner fabric **50a** laminated to foam **50b**, and the liner fabric **50a** is configured to contact the wearer's skin.

Because the inner face of the liner fabric **50a** is in direct contact with the wearer's skin, it is therefore a soft, comfortable fabric, such as polyester or some type of blend. In one example, the liner fabric **50a** is made of 100% polyester weft knit interlock and has a weight of 95 g/m<sup>2</sup> having 48 courses per inch and 52 wales per inch (32 gauge). The outer face of the liner fabric **50a** is laminated to foam **50b** prior to assembly with the remainder of the bra cup **12a**. The foam **50b** is coextensive with the liner fabric **50a**. In one example, prior to molding the bra cup **12a**, the foam **50b** has a uniform thickness along the height of the bra cup **12a** and is about 2 mm thick. The foam **50b** can be medium density stretch foam, and in one example has a density of 45 kg/m<sup>3</sup>.

Turning to the outer side **28**, the bra cup **12a** also includes an outer layer **52** opposing the inner layer **50**. In the example shown herein, the outer layer **52** of the bra cup **12a** comprises a spacer fabric. As is known, spacer fabrics are three-dimensional fabrics that have an inner face layer, an outer face layer, and a pile/connecting layer. Here, the outer face layer is shown at **52a**, and is left exposed rather than covered with another layer of fabric. The outer face layer **52a** can be a solid color (FIG. 11) or can be printed with a pattern (FIG. 10). The pattern can be printed directly onto the outer face layer **52a** of the spacer fabric outer layer **52** after the spacer fabric is knit. In this example, the pile/connecting layer is not died or printed, but only the outer face layer **52a** is printed. The layers of the spacer fabric outer layer **52** can be knitted with polyethylene terephthalate (PET), polyurethane (PU), and/or polyester fibers, among other types of fibers that provide stretch and breathability to the spacer fabric outer layer **52**.

The opposite, inner face layer **52b** of the spacer fabric outer layer **52** is directly molded to a shaping foam layer **54**. The shaping foam layer **54** is sandwiched between the outer layer **52** and the inner layer **50** of the bra cup **12a** and the shaping foam layer **54** extends from the lower edge **17a** of the bra cup **12a** to the upper edge **15a** of the bra cup **12a**. The shaping foam layer **54** can be medium density stretch foam, and in one example has a density of 45 kg/m<sup>3</sup>. The thickness of the shaping foam layer **54**, before it is molded as part of the bra cup **12a**, ranges from about 1 mm to about 5 mm, depending on what part of the bra cup **12a** it forms. In one example, the shaping foam layer **54** is 2 mm thick before being molded. This uniform thickness may continue up the bra cup **12a** to a location approximately halfway between an apex **39** of the bra cup **12a** and the upper edge **15a**. Thereafter, the thickness of the shaping foam layer **54** tapers off drastically toward the upper edge **15a** of the bra cup **12a** to provide a smooth neckline transition.

It can be seen that the thickness of the liner fabric **50a** is roughly the same along the entire height of the bra cup **12a**, while the foam **50b** of the inner layer **50**, the shaping foam layer **54**, and the spacer fabric outer layer **52** are relatively thicker in some areas as opposed to others. For instance, near the neckline **14** at the upper edge **15a** and near the torso band **24** at the lower edge **17a**, the spacer fabric outer layer **52** and the foam layers **50b**, **54** become thinner. This relative change in thickness can be achieved by molding of the cup, for example, if the male and female halves of the mold are closer to one another at the upper and lower edges **15a**, **17a** than in the area of the bra cup **12a** configured to be situated immediately under the wearer's breasts, in the creases between her breasts and her torso. Thus, both the way the bra cup **12a** is molded and the pre-molding thickness differential of a given layer can influence the final thickness of that given layer.

In addition to having foam layers **50a**, **54** that are of different thicknesses in different areas before and/or after being molded, the bra cup **12a** can also include a covering foam layer **58** sandwiched between the shaping foam layer **54** and the inner layer **50**. A separate piece of foam can be provided for each bra cup **12a**, **12b** as the covering foam layer **58**. (See FIG. 8, pieces **58a**, **58b**.) The covering foam layer(s) **58** is/are centered at the apex **39** of each respective bra cup **12a**, **12b**. The covering foam layer **58** can be relatively high density foam in comparison to the other foam layers so as to provide coverage and prevent nipple show-through. In another example, the covering foam layer **58** includes a layer of 100% spandex laminated to a layer of foam. Because the spacer fabric outer layer **52** and the shaping foam layer **54** are provided up the entire height of the bra cup **12a**, these layers **52**, **54** work together with the covering foam layer **58**, which can be as thick as 4 mm, to provide modesty to the bra cup and further prevent nipple show-through.

Each of the layers of the bra cup **12a** described herein above is also shown in FIG. 8, which shows the layers that make up both bra cups **12a** and **12b** as they would be placed in a mold having a male half **60a** and a female half **60b**. The layers making up a support shelf assembly **56**, configured to be situated immediately under the wearer's breasts, are also shown in FIG. 8. Referring now to both FIGS. 3 and 8, the support shelf assembly **56** spans across at least a lower portion of each bra cup **12a**, **12b**, for example, in an area located below the apexes **39** and above (or extending to) the lower edges **17a**, **17b** of the bra cups **12a**, **12b**. The support shelf assembly **56** comprises a plastic support component **62** located proximate the lower edge **17a**, **17b** of each respective bra cup **12a**, **12b**. In this example, the support component **62** is an undulating, W-shaped molded body configured to support an underside of the wearer's breasts. In cross-section, the support component **62** has a crescent shape that mimics the crease under the wearer's breasts. A non-stretch stabilizer fabric layer **64** spans between both bra cups **12a**, **12b** and along the support component **62**. A first supportive foam layer **66** also spans between both bra cups **12a**, **12b** and along the support component **62**. The support shelf assembly **56** further comprises a second supportive foam layer **68** spanning between both bra cups **12a**, **12b** and along the support component **62**. The second supportive foam layer **68** is located on an opposite side (here, an inner side) of the support component **62** than the first supportive foam layer **66**.

In the present embodiment, the stabilizer fabric layer **64**, the first supportive foam layer **66**, and the second supportive foam layer **68** of the support shelf assembly **56** all have an undulating shape that mimics a curvature of an underside of the wearer's breasts. The stabilizer fabric layer **64** extends along a full length of the support component **62**. Note that in the present embodiment, the stabilizer fabric layer **64**, the first supportive foam layer **66**, and the second supportive foam layer **68** of the support shelf assembly **56** are each single, continuous layers of material spanning both of the bra cups **12a**, **12b** and extending along the full length of the support component **62**, which arrangement provides structural integrity to the supportive portion of the bra cups **12a**, **12b**. Note too that the inner and outer layers **50**, **52** and the shaping foam layer **54** of each bra cup **12a**, **12b** and the first supportive foam layer **66**, the second supportive foam layer **68**, and the stabilizer fabric layer **64** of the support shelf assembly **56** all extend below a lower edge **63** of the support

assembly **56**, beyond that which a bendable, moldable plastic support component **62** could provide on its own. This is especially so given that the support shelf assembly **56** is molded between the inner and outer layers **50**, **52** of each bra cup **12a**, **12b** such that the support shelf assembly **56** is an embedded, integral part of the front panel **11**. This molding/embedding process will be described further herein below.

In the present example, referring also to FIGS. 1 and 10, the inner and outer layers **50**, **52** and the shaping foam layer **54** of each bra cup **12a**, **12b** and at least the first supportive foam layer **66** and the stabilizer fabric layer **64** of the support shelf assembly **56** all extend to the lower edge **17a**, **17b** of each bra cup **12a**, **12b** and are coupled to the elastic torso band **24**. This provides stability and relative stiffness not only in the immediate area of the support component **62**, but also beneath the support component **62**, because the support shelf assembly **56** extends below the wearer's breasts and lays flat against her torso (see FIG. 10). Such relative stiffness, when compared to the remainder of the bra cups **12a**, **12b**, prevents the portion of the bra cups **12a**, **12b** below the support component **62** from folding over due to the weight of the wearer's breasts and/or movement thereof during exercise. Additionally, such an arrangement allows the layers **64**, **66**, **68** of the support shelf assembly **56** to provide additional support to that already provided by the support component **62** without adding bulk or weight near the tops of the bra cups **12a**, **12b**.

The first supportive foam layer **66** is provided on the outer face of the support component **62** and provides extra support thereto. In one example, the first supportive foam layer **66** is about 3 mm thick prior to molding and has a density of 45 kg/m<sup>3</sup>. In another example, the first supportive foam layer **66** is not provided, and instead the shaping foam layer **54** is thicker in the area along the support component **62**.

The second supportive foam layer **68** provides extra padding between the support component **62** and the wearer's chest, in order to provide comfort to the wearer. The second supportive foam layer **68** also provides extra support to the underside of the wearer's breasts. In another example, the foam **50b** of the inner layer **50** is thicker near where it is molded to the support component **62** via the stabilizer fabric layer **64**, and the bra cup **12a** does not include a second supportive foam layer **68**. However, if a second supportive foam layer **68** is provided, this second supportive foam layer **68** can have the same or a different density than the foam **50b** of the inner layer **50**, and the padding and support of the support shelf assembly **56** can thereby be controlled. In one example, the second supportive foam layer **68** is about 5 mm thick prior to molding and has a density of 45 kg/m<sup>3</sup>.

The stabilizer fabric layer **64** is provided between the second supportive foam layer **68** and the foam **50b** of the inner layer **50**. The stabilizer fabric layer **64** provides the support shelf assembly **56** with extra support and creates a more stable bond between the foam **50b** and the foam **68**. In another example, the stabilizer fabric layer **64** and the second supportive foam layer **68** are swapped, such that the stabilizer fabric layer **64** is immediately next to the support component **62**. The stabilizer fabric layer **64** is made of non-stretch fabric, which provides support to the wearer's breasts. In one example, the stabilizer fabric layer **64** is made of 100% polyester weft knit interlock and has a weight of 100 g/m<sup>2</sup> having 48 courses per inch and 48 wales per inch (28 gauge). In another example, the stabilizer fabric layer **64** is made of 100% polyester weft knit interlock and has a weight of 95 g/m<sup>2</sup> having 48 courses per inch and 52 wales per inch (32 gauge).

When constructing the bra cups **12a**, **12b** of the present disclosure, the spacer fabric outer layer **52** may be pre-molded into the desired cup shapes. Prior to such pre-molding, the spacer fabric outer layer **52** may be laminated to the shaping foam layer **54** using, for example, one or all of heat, pressure, and spray adhesive. The support component **62** may also be pre-molded into the undulating W-shaped body. The liner fabric **50a** and the foam **50b** of the inner layer **50** are also pre-laminated together. Next, referring to FIG. **8**, the pre-molded spacer fabric outer layer **52**, the shaping foam layer **54**, the first supportive foam layer **66**, the pre-molded support component **62**, the second supportive foam layer **68**, the stabilizer fabric layer **64**, the covering foam layer pieces **58a**, **58b**, and the laminated inner layer **50** are placed together in the mold **60a**, **60b**. The layers are molded to the desired shape while being heated to a desired temperature. During the molding process, the plastic support component **62** is directly fused to the first and second supportive foam layers **66**, **68**, or to the stabilizer fabric layer **64** if no second supportive foam layer **68** is provided. Thus, the support component **62** does not shift within the cups, but rather is embedded in place in the cups. In effect, the support component **62** acts as a relatively stiffer area of the cups, and poke through, breakage, or other negative occurrences associated with normal underwires are thereby avoided because the support component **62** is an integral part of the molded bra cups **12a**, **12b**. Because the support component **62** is molded directly to cushioning, padded materials, this provides extra comfort for the wearer.

In the example shown in FIG. **8**, the mold **60a**, **60b** is shaped to form both of the bra cups **12a**, **12b** and the center gore **16** at once, thereby forming the entire front panel **11** of the bra **10**. After the bra cups **12a**, **12b** are molded, other fabric layers can be stitched to the molded bra cups **12a**, **12b**, for example after being molded separately themselves. Next, the molded front panel **11** is cut to size and provided with trim, which can be sewn or laminated around the edges **13a**, **13b**, **15a**, **15b**, **17a**, **17b** of the bra cups **12a**, **12b**. As described herein above, the torso band **24** can be sewn and/or laminated to the lower edges **17a**, **17b** of the bra cups **12a**, **12b** to provide a finished edge. The wings **22a**, **22b** can be later sewn or otherwise connected to the outer edges **13a**, **13b** of the bra cups **12a**, **12b**. The fabric pieces **19a**, **19b** can be used to connect the upper edges **15a**, **15b** to the straps **20a**, **20b**. In another embodiment, the front panel **11** can be cut apart at the center gore **16** to form two separate bra cups **12a**, **12b**, which can then be re-connected with a zipper or other closure, as will be described further herein below with respect to FIG. **11**.

FIG. **4** shows an alternative example of a cross section of a bra cup **110** according to the present disclosure. Starting at the outer side **28**, the bra cup **110** includes a outer layer comprising a spacer fabric **132**. The inner face layer of the spacer fabric **132** is directly molded to a shaping foam layer **136**. Similar to the first embodiment, the shaping foam layer **136** reaches to the same height as the spacer fabric **132**, but its thickness tapers off drastically toward the upper edge **15a** of the bra cup **110**. The thickness of the shaping foam layer **136** also tapers off dramatically toward the lower edge **17a** of the bra cup **110**, so as not to add bulk or weight in this area. An inner face of the shaping foam layer **136** can be directly molded to a plastic support component **138**. The thickness of the shaping foam layer **136**, even before it is molded as part of the cup **120**, ranges from about 8 mm to about 1 mm, depending on what part of the bra cup **110** it forms. In one example, the shaping foam layer **136** is 8 mm thick where it contacts the support component **138** in order

to provide extra support in this area. The inner side **30** of the bra cup **110** includes an inner layer comprising a liner fabric **140** laminated to foam **142**. In one example, prior to molding the bra cup **110**, the foam **142** has a uniform thickness along the height of the bra cup **110** and is about 1 mm thick. Again, similar to the first embodiment, the thickness of the liner fabric **140** is roughly the same along the entire height of the cup **120**, while the foams **136**, **142** and the spacer fabric **132** are relatively thicker in some areas as opposed to others. For instance, near the neckline at the upper edge **15a**, the spacer fabric **132** and the foam layers **136**, **142** become thinner. A supportive foam layer **144** is sandwiched between the foam **142** and the support component **138**. The supportive foam layer **144** provides extra padding and extra support to the underside of the wearer's breasts. A stabilizer fabric layer **146** is provided between the supportive foam layer **144** and the support component **138**. The stabilizer fabric layer **146** provides the support component **138** with extra support and with a more stable bond to the supportive foam layer **144**.

FIG. **9** shows the layers of the second embodiment of the bra cup **110** as they would be placed in between the halves **60a**, **60b** of a mold. Note that in this example, the support component **138** includes two separate halves **138a**, **138b**. More specifically, the support component **138** comprises two lateral halves **138a**, **138b**, each half of the support component being a U-shaped molded body configured to support an underside of a respective one of the wearer's breasts. This type of support component **138** might be desirable if the bra cups are to be used in a front-close bra such as a bra with a zipper up the front connecting the two bra cups at the center gore **16**. (See FIG. **11**.) Note that together, the two support components **138a**, **138b**, the stabilizer fabric layer **146**, and the supportive foam layer **144** make up a support shelf assembly.

FIG. **5** illustrates a cross section of another alternative embodiment of a bra cup **220** according to the present disclosure. In this example, the layers of the bra cup **220** will be referred to generically, as the layers may be either fabric or foam in different examples. An outer layer of the bra cup **220**, denoted as **248**, may be a spacer fabric. A layer **250** laminated to the inner surface of the spacer fabric outer layer **248** may be a fabric layer or a foam layer. If a fabric layer, the fabric may be made of polyester. Another layer **252**, laminated to the inside surface of the layer **250**, can be a foam layer or a stabilizer layer. If a stabilizer layer, the layer **252** is made of fabric. A layer **254** just next to the layer **252** can be a supportive foam layer. The support component is shown at **256**. Another supportive foam layer **258** can be provided on the opposite side of the support component **256**. Together, the layers **252**, **254**, **256**, and **258** make up a support shelf assembly. As the inner layer, a foam layer can be provided at **260**, which can be laminated to a liner fabric layer **262**, which serves as the inner face of the bra cup **220**. The outer layer **248** comprises the exposed outer side **28** of the bra cup **220**, while the layer **262** comprises the entire inner side **30** of the bra cup **220** that contacts the wearer's skin. The foam or fabric layer shown at **250** extends almost for the entire height of the bra cup **220**, but ends just before the upper edge **15a** and the lower edge **17a**. The foam layer shown at **260** extends for the entire height of the bra cup **220**, but tapers in thickness at both the upper and lower edges **15a**, **17a** of the bra cup **220**. The foam layers shown at **254** and **258** extend vertically only in the general area of the support component **256**. The stabilizer fabric layer **252** extends only on one side of the support component **256**, and generally only for the height of the support component **256**.

FIG. 6 shows a cross section of yet another example of a bra cup 330 according to the present disclosure. The bra cup 330 includes an outer layer 302 comprising a spacer fabric. A shaping foam layer 304 is situated on an inner face of the spacer fabric outer layer 302. An inner layer of the bra cup 330 includes a fabric liner 314 laminated to foam 312. A support shelf assembly is made of a support component 306, a stabilizer fabric layer 308, and a supportive foam layer 310. In one example, the stabilizer fabric layer 308 comprises one layer of stabilizer fabric. In another example, two layers of stabilizer fabric may be provided for extra support, such as for use in a bra having a large cup size. The two layers of stabilizer fabric can be provided face-to-face, or one layer of stabilizer fabric can be provided on each side of the support component 306. Together, the support component 306 and layers 308 and 310 make up a support shelf assembly.

FIG. 7 shows a cross section of yet another alternative embodiment of a bra cup 440. In this example, an outer layer 402 comprises a spacer fabric. A stabilizer fabric, which can be provided in one or multiple layers, is shown at 404. The inner layer of the bra cup 440 comprises foam 406 laminated to a liner fabric layer 408. The bra cup 440 is also provided with a covering foam layer 410 near the apex 39, which provides padding to prevent nipple show-through. This bra cup 440 may be used in a bra having a small cup size, as it lacks a plastic support component.

FIG. 10 shows one example of the sports bra 10 of the present disclosure as worn on a wearer, wherein one bra cup 12a, 12b supports each of her breasts. FIG. 11 shows an alternative example of a sports bra 100. The front panel of the bra 100 comprises two lateral halves 102a, 102b, each half of the front panel comprising one of the bra cups 12a or 12b. In this example, the sports bra 100 includes a front closure, which here is a zipper 101. The zipper 101 on the center gore 16 couples the two halves 102a, 102b of the front panel together. A back connector 26 (see FIG. 2) may or may not be provided in addition to the front zipper 101. Other types of front closures, such as hook and eye closures, Velcro, snaps, etc. could be provided. Both of the sports bras 10, 100 may have front panels 11 with bra cups 12a, 12b as described with respect to FIGS. 1, 3, and 8, or front panels with bra cups like those described with respect to FIGS. 4-7 and 9. If the bra cups 12a, 12b are formed as described with respect to FIGS. 1, 3, and 8 (the first embodiment), note that each bra cup 12a, 12b includes an inner layer 50, outer layer 52, and shaping foam layer 54 and a stabilizer fabric layer 64 and first supportive foam layer 66 of a support shelf assembly 56 that span across a center gore 16 that connects the bra cups 12a, 12b and together form a front panel 11 of the bra 10, 100. In other words, the front-close sports bra 100 of FIG. 11 could be made by molding layers of single, continuous pieces of fabric and foam that span across both bra cups 12a, 12b, and later cutting those foam and fabric layers into halves 102a, 102b after the front panel of the bra 100 has been molded. In an alternative embodiment, the sports bra 100 can be formed by molding previously-cut layers of foam and fabric according to the above-described cross-sections into separate lateral halves 102a, 102b of the front panel.

In either of the bras of FIG. 10 or 11, the support component could be the undulating, W-shaped molded body 62 shown in FIG. 8, which because it is plastic, is easily cut to form the lateral halves 102a, 102b of the sports bra 100. Alternatively, the support component could be the separate, U-shaped components 138a, 138b shown in FIG. 9, which would obviate the need to cut the support component when

cutting the center gore 16 to create the two lateral halves 102a, 102b of the front panel. Note that the separate support component halves 138a, 138b might be used even in the sports bra 10, which is not separable at the center gore 16. Both of the sports bras 10, 100 allow for a plunging neckline while still providing good support that controls and contains the wearer's breasts. The bras 10, 100 deliver on maximum support with less construction, and yet remain lightweight due to inclusion of a plastic support shelf and a spacer fabric.

FIG. 12 shows an example of a lingerie-type bra 70 according to the present disclosure. The bra 70 also includes two bra cups 72a, 72b, which are connected by a center gore 74. The cross section of both of the bra cups 72a, 72b can be that shown and described with respect to any of FIGS. 3-7, it being understood that the relative height and thickness of the support shelf assemblies shown therein might not be as high or as thick as those shown for purposes of the sports bras 10, 100. A center gore 74 corresponding to the exemplary bra cup 110 of FIGS. 4 and 9 is shown in cross section in FIG. 13. Similar to the bra cups 72a, 72b, the outer side 76 of the center gore 74 comprises a spacer fabric, as shown at 78. The spacer fabric 78 may be coextensive (integral) with the spacer fabric of the bra cups 72a, 72b. A stabilizer fabric layer, which provides relative stiffness to the center gore 74, is shown at 80. The stabilizer fabric layer 80 can be, for example, 100% polyester weft knit interlock with a weight of 100 g/m<sup>2</sup> and 48 courses per inch and 48 wales per inch (28 gauge) and can be coextensive (integral) with stabilizer fabric layer 146 shown in FIGS. 4 and 9. A foam layer is shown at 82. This foam layer 82 can be coextensive (integral) with corresponding supportive foam layer 144. Another foam layer is shown at 84, which can be coextensive (integral) with corresponding foam 142. At an inner side 88 of the center gore 74, a fabric liner 86 is provided, which can be coextensive (integral) with the liner fabric 140. It should be understood that if the cup cross sections of FIG. 3 or 5-7 are instead used, the center gore 74 would have corresponding layers integral with the cup layers shown in those figures.

In the above description, certain terms have been used for brevity, clarity, and understanding. No unnecessary limitations are to be implied therefrom beyond the requirement of the prior art because such terms are used for descriptive purposes only and are intended to be broadly construed. The different articles and methods described herein above may be used in alone or in combination with other articles and methods. Various equivalents, alternatives and modifications are possible within the scope of the appended claims. The scope of this disclosure is not intended to be bound by the literal order or literal content of method steps described herein, and non-substantial differences or changes still fall within the scope of the disclosure.

What is claimed is:

1. A brassiere comprising:

- a pair of bra cups, each bra cup in the pair of bra cups configured to hold one of a wearer's breasts;
- each bra cup having an inner layer configured to contact the wearer's skin;
- each bra cup having an outer layer opposing the inner layer;
- each bra cup having a shaping foam layer sandwiched between the inner and outer layers of the respective bra cup, wherein the shaping foam layer extends from a lower edge of the respective bra cup to an upper edge of the respective bra cup; and
- each bra cup having a support shelf assembly between the inner and outer layers of the respective bra cup and



## 11

spanning across at least a lower portion of the respective bra cup, the support shelf assembly comprising:  
 a plastic support component located proximate the lower edge of the respective bra cup;  
 a non-stretch stabilizer fabric layer located along a full length of the support component;  
 a first supportive foam layer located along the support component; and  
 a second supportive foam layer located along the support component, the second supportive foam layer being located on an opposite side of the support component than the first supportive foam layer;  
 wherein the inner layer, the outer layer, the support shelf assembly, and the shaping foam layer are molded together such that the support shelf assembly is an embedded, integral part of the lower portion of the respective bra cup, and during the molding process, the support component is directly fused to at least one of the first supportive foam layer and the second supportive foam layer on either side of the support component.

2. The brassiere of claim 1, wherein during the molding process, the support component is directly fused to both the first supportive foam layer and the second supportive foam layer on either side of the support component.

3. The brassiere of claim 1, wherein the stabilizer fabric layer is located on an opposite side of the second supportive foam layer than the support component, and during the molding process, the second supportive foam layer is directly fused to the stabilizer fabric layer.

4. The brassiere of claim 1, wherein the support component is an undulating, W-shaped molded body configured to support an underside of the wearer's breasts.

5. The brassiere of claim 1, wherein the stabilizer fabric layer, the first supportive foam layer, and the second supportive foam layer of the support shelf assembly all have an undulating shape configured to mimic a curvature of an underside of the wearer's breasts.

6. The brassiere of claim 1, wherein the brassiere comprises two lateral halves, each half of the brassiere comprising one of the bra cups, and further comprising a zipper that couples the two halves of the brassiere together.

7. The brassiere of claim 6, wherein the support component comprises two lateral halves, each half of the support component being a U-shaped molded body configured to support an underside of a respective one of the wearer's breasts.

8. The brassiere of claim 1, wherein:  
 the inner layer of each bra cup comprises an inner liner fabric laminated to an inner foam layer, and the inner liner fabric is configured to contact the wearer's skin; and  
 the stabilizer fabric of the support shelf assembly comprises 100% polyester.

9. The brassiere of claim 1, wherein the inner and outer layers and the shaping foam layer of each bra cup and the first supportive foam layer, the second supportive foam layer, and the stabilizer fabric layer of the support shelf assembly all extend below a lower edge of the support component.

10. A brassiere comprising:  
 a pair of bra cups, each bra cup in the pair of bra cups configured to hold one of a wearer's breasts;  
 an inner layer of the pair of bra cups configured to contact the wearer's skin;  
 an outer layer of the pair of bra cups opposing the inner layer;

## 12

a support shelf assembly of the pair of bra cups between the inner and outer layers of the pair of bra cups and spanning across at least a lower portion of each bra cup, the support shelf assembly comprising:  
 a plastic support component located proximate a lower edge of each bra cup;  
 a first supportive foam layer located along a first side of the support component;  
 a second supportive foam layer located along an opposite second side of the support component; and  
 a non-stretch stabilizer fabric layer located along the second side of the support component;  
 wherein the inner layer, the outer layer, and the support shelf assembly are molded together such that the support shelf assembly is an embedded, integral part of the lower portion of each bra cup, and during the molding process, the support component is directly fused to at least one of the first supportive foam layer, the second supportive foam layer, and the stabilizer fabric layer on either side of the support component.

11. The brassiere of claim 10, wherein the stabilizer fabric layer is located on an opposite side of the second supportive foam layer than the support component.

12. The brassiere of claim 11, wherein during the molding process, the support component is directly fused to the first supportive foam layer and the second supportive foam layer on either side of the support component, and the stabilizer fabric layer is directly fused to the opposite side of the second supportive foam layer.

13. The brassiere of claim 10, further comprising a shaping foam layer of the pair of bra cups sandwiched between the inner and outer layers of the pair of bra cups, wherein the shaping foam layer extends from the lower edge of each bra cup to an upper edge of each bra cup.

14. The brassiere of claim 10, wherein the support component is an undulating, W-shaped molded body configured to support an underside of the wearer's breasts.

15. The brassiere of claim 10, wherein the stabilizer fabric layer is made of 100% polyester weft knit interlock.

16. A brassiere comprising:  
 a pair of bra cups, each bra cup in the pair of bra cups configured to hold one of a wearer's breasts;  
 an inner layer of the pair of bra cups configured to contact the wearer's skin;  
 an outer layer of the pair of bra cups opposing the inner layer; and  
 a support shelf assembly between the inner and outer layers of the pair of bra cups and spanning across at least a lower portion of each respective bra cup, the support shelf assembly comprising:  
 a plastic support component located proximate a lower edge of each respective bra cup;  
 a non-stretch stabilizer fabric layer spanning between both bra cups and along a full length of the support component; and  
 a first supportive foam layer spanning between both bra cups and along the support component; and  
 a shaping foam layer sandwiched between the inner and outer layers of the pair of bra cups, wherein the shaping foam layer extends from the lower edge of each respective bra cup to an upper edge of each respective bra cup;  
 wherein the inner layer, the outer layer, the support shelf assembly, and the shaping foam layer are molded together such that the support shelf assembly is an embedded, integral part of the lower portion of each

respective bra cup, and during the molding process, the support component is directly fused to the first supportive foam layer.

17. The brassiere of claim 16, further comprising a second supportive foam layer spanning between both bra cups and along the support component, the second supportive foam layer being located on an opposite side of the support component than the first supportive foam layer. 5

18. The brassiere of claim 17, wherein the stabilizer fabric layer is located on an opposite side of the second supportive foam layer than the support component. 10

19. The brassiere of claim 18, wherein during the molding process, the support component is directly fused to the first supportive foam layer and the second supportive foam layer on either side of the support component, and the stabilizer fabric layer is directly fused to the opposite side of the second supportive foam layer. 15

20. The brassiere of claim 16, wherein the first supportive foam layer is between the shaping foam layer and the support component. 20

\* \* \* \* \*